

TEO ATTACHED

		REVISIÓNS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-1 PULLER SLOT HOLES INCREASED TO Ø1/4 & WALL THINNED FOR FLEXABILITY, -3 RING SHORTENED & GROVE MOVED TO ALLOW -1 PULLER TEETH TO FULLY EXPAND, -7 ILLUMINATED, -9 CROSS BAR WIDTH INCREASED TO 1 FOR ADDED STRENGTH.	2/12/2003		
2		ADDED NEW BOM, TITLE BLOCK, & REV. TABLE. RE-ORGANIZED DWG.'S AND CORRECTED ERRORS. CREATED AN ASSEMBLY DWG, AND CONBINED TWO FILES.	11/20/2007	WP	RW
3		CH'D -9 HOLE FROM Ø.250 (X2) TO Ø.257 (X2) SER S.E.	12/29/2011	RJC	SE
4	15-0472	-9 CH'D ENGRAVE NOTE TO T/N, S/N, "MADE IN USA". UPDATED TO NEW DRAFTING STANDARDS.	1/5/2016	SM	JAG






NOTE: 1. USED ON BELL MODELS 206A, B, L1-L4. SEAL #406-340-104-101

ASSY QTY	ASSY QTY	В/О	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	TITLE	IN IE //
			-1	1	PULLER	H13		2	ENG	111/5/0
			-3	1	RING	DOM		3	DWG NO.	
		B/O	-5	1	SCREW	STEEL	1/2-20 UNF X 4 IN THREADED ROD (MCMASTER-CARR # 98750A483) MODIFIED	4	MAT'L	
			-9	1	CROSS BAR	1018/1020 CR		5	HEAT TREAT	
			-11	2	UPRIGHT	1018/1020 CR		6	FINISH	
		B/O	-13	2	BTN-HEAD SKT CAP SCR	STEEL	1/4-20 UNC X 1 (MCMASTER-CARR # 91255A542)	1	SPEC	
		B/O	-15	1	JAM NUT	STEEL	1/2-20 JAM NUT (MCMASTER-CARR # 94846A525)	1	DRAWN BY: CHECKED:	COLE
		B/O	-17	1	TALL NUT	STEEL	1/2-20 UNF (MCMASTER-CARR # 90565A330)	1	OPPS APPR:	ANDE
		B/O	-19	1	THRUST BEARING	STEEL	APPLIED # NTA-815	1	QA APPR:	LIND
		B/O	-21	2	BEARING WASHER	STEEL	APPLIED # TRA-815	1	APPROVED:	GILBI
		B/O	-23	2	BALL PLUNGER	S.S.	10-32 X 33/64 (MCMASTER-CARR # 3408A94)	1	SCALE	2:3


DART


"ENGINE/GEARBOX SEAL PULLER

3	DWG NO.		RB	8T 1	8560		REV 4
4 5	MAT'L HEAT TREAT					S OTHERWISE SPECI NSIONS ARE IN INCH FRACTIONS ± 1/8	
6	FINISH SPEC				.XX ± .01 .X ± .1		125/
1	DRAWN BY: CHECKED:	COLE	FLDT		.015 x 45° C	OR .015R NAL LIMITS APPLY	
	OPPS APPR:	ANDERS				T DIM AND TOL PER	
1	QA APPR:	LINDSA	·Υ			USED ON MODEL	
1	APPROVED:	GILBEF	₹T			SEE NOTE 1	
1	SCALE	2:3	DATE	5/	2/2002	SHEET 1 OF	6




		REVISIONS REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED





SCALE

1:1



DART

ENGINE/GEARBOX SEAL PULLER

DWG NO. RBT18560-3 MAT'L DOM UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ HEAT TREAT FINISH BLACK OXIDE SPEC A T.I.

1. BREAK ALL SHARP EDGES

.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 DRAWN BY: COLE CHECKED: OPPS APPR: QA APPR: USED ON MODEL APPROVED: WEIL SEE SHT 1


5/2/2002


SHEET 3 OF 6



RING

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED







ENGINE/GEARBOX SEAL PULLER

5/2/2002

SHEET 4 OF 6

RBT18560-5 MAT'L STEEL UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ HEAT TREAT FINISH BLACK OXIDE SPEC A T.I.

1. BREAK ALL SHARP EDGES

.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 DRAWN BY: COLE CHECKED: OPPS APPR: QA APPR: USED ON MODEL APPROVED: WEIL SEE SHT 1


DWG NO.


SCALE


1:1

SCREW

		REVISIONS			
REV	ECR	DATE	INITIAL	APPROVED	
3		CH'D -9 HOLE FROM Ø.250 TO Ø.257 PER S.E.	12/29/2011	RJC	SE
4	15-0472	CH'D -9 ENGRAVE NOTE TO: T/N, S/N, "MADE IN USA"	1/5/2016	SM	







APPROVED:

SCALE

WEIL

1:1

"ENGINE/GEARBOX SEAL PULLER

5/2/2002

SEE SHT 1

SHEET 5 OF 6

(-9)

CROSS BAR

REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. ECR DESCRIPTION DATE INITIAL APPROVED $\emptyset.50 -$ 1/4-20 UNC - 2B ▼ .63 -- 3.25 -



ENGINE/GEARBOX SEAL PULLER

RBT18560-11 MAT'L 1018/1020 CR TREAT FINISH BLACK OXIDE SPEC DRAWN BY: COLE CHECKED:

DWG NO.

UNLESS OTHERWISE SPECIFIED SURFACES = 125

A T.I.


1. BREAK ALL SHARP EDGES

.015 x 45° OR .015R

2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 OPPS APPR:

QA APPR: USED ON MODEL APPROVED: WEIL SEE SHT 1 SCALE 3:2 5/2/2002 SHEET 6 OF 6

UPRIGHT



MATERIAL NEED UPDATED

TRANSACTION CODE (TC):

C-CREATE

D-DELETE

A-ADD

R-REVISE

REASON:

WAS: PART# RBT18560-3 Rev 4 MATERIAL: DOM

IS: PART# RBT18560-3 Rev 4 MATERIAL: A513 TUBING AS PER MT-A513-T

SHEET 1 OF 1

DATE 17.09.07

COPYRIGHT © 2017 BY DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE

USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION

FROM DART AEROSPACE LTD.

DRAWN: VM 09/25/2017

DOCUMENTS EFFECTED: PATTERN INSTALL INSTRUCTIONS X BOM